


AQUATIC ACCESS INC.

DIMENSIONAL WORKSHEET for IN-GROUND Pools/Spas

PLEASE COMPLETE A DIMENSIONAL WORKSHEET FOR EACH LIFT/LOCATION.

Remember to allow open space between the lift and the pool corner or other obstruction to the lift's rotation (a minimum of 36" needed for all IGAT models), as well as room for any mobility device beside the lift. Always confirm lift and socket location with Aquatic Access engineers or instruction manual before installing.


Draw in desired location and seat rotation of lift on this drawing. If shape differs, provide your own sketch. Indicate location of any steps, lights, ladders, benches, handrails or other obstructions to lift rotation on deck or within pool walls.



١.	Verify with a carpenter's level (see illustration below) the amount of deck's slope at 22" from pool edge								
2.	What is the composition of the deck aro	und the poo	l and the po	pol wall?					
3.	Is there a vinyl liner in the pool?	YES	NO						
4.	Is the pool deck on a solid foundation?	YES	NO	If no, provide cross-section details on separate page.					
5.	Does the pool have a pool cover?	YES	NO	If yes, provide cross section details on separate page.					
6.	Is the pool located indoors?	YES	NO	If yes, how high is the ceiling?					
7.	Is the location on city water?	YES	NO	What is the water pressure?PSI					
8.	Is the pool filled with salt water?	YES	NO						
9.	What is the weight of the heaviest user of	of the lift?							
10.	Choose the color of the lift's seat.	WHITE	BLUE						
11	Armrosts — For Sido Facing Soats one stationary cylinder side armrost and one flip up outer armrost are standard								

DIMENSIONAL INFORMATION REQUIRED FOR IN-GROUND POOLS

Select the pool profile drawing that best matches your pool below and fill in the requested measurements. If none of these profiles represent your pool, please make a detailed sketch with the pertinent measurements.



A = 0 For a Level Deck

Contact Person .		Company Name	Company Name		
Address					
Ph.	Fax	E-Mail			

Email: CustomerService@AquaticAccess.com. MAIL OR FAX COMPLETED FORM TO:

^{11.} Armrests -- For Side-Facing Seats, one stationary cylinder-side armrest, and one flip-up outer armrest are standard. For Front-Facing Seats (ylinder behind seat), two stationary armrests are standard. Other configurations, or no armrests can be ordered.